
AirTech

less plastic than standard 9″ diffuser

With 45%

9" fine bubbles disc diffuser with EPDM membrane and integrated ring



Ø 257



04059
257
3/4″ NPT
0,43

Performance

Code	04059
Minimum airflow [Nm³/h]	1,0
Nominal airflow [Nm³/h]	3,5
Maximum airflow [Nm³/h]	7,0
Design airflow range [Nm³/h]	2,0-4,0
* Head losses [cm w.c.]	39,0

* Head losses are calculated at nominal airflow and 4m submergence

Materials

Code	04059
Membrane	EPDM
Holder with integrrated retainer ring	PPGF 30%

 Holder with integrated retainer ring Membrane 	
Membrane	
Code	
Number of slits	
Perforation [mm]	
Active surface [m ²]	
Average thickness [mm]	

04059 NOTES

3/4" NPT M

2

~46

1

>5.000 SOTE according 1,-1,5 to EN 12255-15 (or ANSI/ASCE 2-06) Tollerances on the 0.0381 thickness ±0,2 mm 2,2 Tensile strenght according >122 to ISO 37 type 1 450 Elongation at break ISO 37 type 1 60 ± 5 < 15



Tensile strength [Kg/cm²]

Elongation at break [%]

Hardness [Shore A]

Plasticizer content [%]